


# Jicamarca Beacon Processing using Open Source Beacon Recording and Processing Package



Anthea Coster, John Swoboda, Phil Erickson, Frank  
Lind, Juha Vierinen, Ryan Volz



**MIT**  
**HAYSTACK**  
**OBSERVATORY**

# Beacon Receiver


- Total Electron Content (TEC), the number of electrons integrated along a line – a columnar measurement (el/m<sup>2</sup>)
- S4,  $\sigma_\phi$  : Indices that measure scintillation



# Beacon Receiver

- Signal Model

- $x(t) = e^{j\omega_0 t + \phi_0(t)}$
- $\phi_0(t) = \frac{\omega_0}{c} \int_0^{L(t)} N_e(s) ds$




- Need two signals

$$\left( \frac{\omega_1}{\omega_0} \phi_0(t) - \phi_1(t) \right) \frac{1}{a} \left( \frac{\omega_1}{\omega_0^2} - \frac{1}{\omega_1} \right)^{-1} = \int_{L_0(t)}^{L(t)} N_e(s) ds + const.$$
$$a = \frac{q^2}{2\epsilon_0 m_e c}$$

Vierinen et al. 2013

Siefring et al. 2011


Bernhardt et al. 2006



**MIT**  
**HAYSTACK**  
**OBSERVATORY**

# Data Collection


- RAPID: Radio Array of Portable Interferometric Devices
- SKALA: Square Kilometer Array Low-Frequency Antenna



RAPID antenna and base





# Data Collection Sites




**HAYSTACK  
OBSERVATORY**



# Black Box



# Signal Processing






# Data Example: 2017-01-15 ~03:45 UT



**MIT**  
**HAYSTACK**  
**OBSERVATORY**




# Residual Example: 2017-01-15 ~03:45 UT





**MIT**  
**HAYSTACK**  
**OBSERVATORY**

# Final TEC Measurement: 2017-01-15 ~03:45 UT


Relative TEC (rTEC - Black Line)






SNR for Both Channels



# Final TEC Measurement



# Comparison of Two Sites – Feb 9, 2017




MIT  
HAYSTACK  
OBSERVATORY

February 9<sup>th</sup> Data



# Beacon Processing Flow

- Radio config contains
  - Center Frequencies,
  - BW,
  - Radio type
  - Number of frequencies
  - Antenna
- Satellite config uses TLEs
  - Used to derive Doppler
- Recording creates metadata and sets up recording processes when satellite is in view



- Recorded data kept for reprocessing purposes
  - Digital RF and Digital Metadata formats allow for long term archival
- If coded wave form can add plugin as part of Doppler correction
- TEC derived from N channels
  - $N \geq 2$

## Current Status/Future



- Processing chain is available with the Digital RF software package
- Develop ways of correlating measurements from different sources
- Extend software for use on inexpensive software defined radios
- Possible future work with cube-sats to get more transmitters

# References

- J. Vierinen, J. Norberg, M. S. Lehtinen, O. Amm, L. Roininen, A. Väänänen, P. J. Erickson, and D. McKay-Bukowski, “Beacon satellite receiver for ionospheric tomography,” *Radio Science*, vol. 49, no. 12, pp. 1141–1152, Dec. 2014.
- C. L. Siefring, P. A. Bernhardt, D. E. Koch, and I. J. Galysh, “Using TEC and radio scintillation data from the CITRIS radio beacon receiver to study low and midlatitude ionospheric irregularities,” *Radio Science*, vol. 46, no. 6, pp. 753–12, Oct. 2011.
- P. A. Bernhardt and C. L. Siefring, “New satellite-based systems for ionospheric tomography and scintillation region imaging,” *Radio Science*, vol. 41, no. 5, pp. 299–14, 2006.
- T. K. Sarkar and A. Taaghola, “Near-field to near/far-field transformation for arbitrary near-field geometry utilizing an equivalent electric current and MoM,” *Antennas and Propagation, IEEE Transactions on*, vol. 47, no. 3, pp. 566–573, 1999.
- F. D. Lind, C. J. Lonsdale, A. J. Faulkner, P. Alexander, and C. Mattmann, “Radio array of portable interferometric detectors (RAPID),” presented at the 2013 IEEE International Symposium on Phased Array Systems and Technology (ARRAY 2013), 2013, pp. 676–683.

# The Science: Scintillation

- Amplitude Scintillation (S4)
  - Root mean square of the intensity of the signal,  $\langle \rangle$  is the ensemble mean,


$$S_4^2 = \left( \langle I^2 \rangle - \langle I \rangle^2 \right) / \langle I \rangle^2.$$

- Phase Scintillation ( $\sigma_\phi$ )
  - The phase shift of a radio wave as it passes through small-scale irregularities in the ionosphere



$$\sigma_\phi = \sqrt{\langle \phi^2 \rangle - \langle \phi \rangle^2}$$




standard deviation of the signal phase



**MIT**  
**HAYSTACK**  
**OBSERVATORY**



spike in scintillation




(From Anthea Coster, MIT Haystack)



# The Science: Total Electron Content (TEC)

- Total Electron Content (TEC)
  - Electron density along a path between a receiver and a satellite
  - Units:  $10^{16}$  electrons/m<sup>2</sup> (1 TECU)



$$\Delta\phi_{12} = c + b \int_{L_0(t)}^{L(t)} N_e(z) dz$$

difference in frequency  
phases of 2 frequencies

phase ambiguity constant


slant TEC

mapping function



$$v(\alpha) \int_S N_e(s) ds \approx \int_V N_e(s) ds$$

Satellite




S

V


Pierce point

Shape function  $p(h)$

Receiver



(From Vierinen et al. 2016)



**MIT**  
**HAYSTACK**  
**OBSERVATORY**